



LMSR-VK WITH PETROL ENGINE

- petrol engine Honda GX 100 2,1
- **kW** at 3.600 rpm
- total weight 170 kg

item number: 313002



LMSR-HK WITH HYDRAULIC ENGINE

- hydraulic engine with 160 bar system pressure
- total weight 160 kg

item number: 314017



LMSR-EK WITH ELECTRIC ENGINE

- electric engine with 220 V voltage total
- weight 170 kg

item number: 313003



●GENERAL INFORMATION ON LMSR-VK / -HK / -EK

- Dynamic Probing DPL, DPM and DPH
- Modular drop weight system with 50 kg out of 500 mm dropping heights maximum
- Maximum blow energy: 245 Joule
- **○** Blows per minute: 15-30
- Dimensions
 785 mm x 780 mm x 2.340 mm

- Adjusting spindle for perpendicular working in all positions
- Blow counter
- Accessoires and all needing tools included
- Window sampling possible with additional three-leg foot

item number: 341323

LMSR-SPT-VK WITH PETROL ENGINE

- petrol engine Honda GX 100 2,1
- **k**W at 3.600 rpm
- total weight 227 kg

item number: 314004



LMSR-SPT-HK WITH HYDRAULIC ENGINE

- hydraulic engine with 160 bar system pressure
- total weight 220 kg

item number: 314006



● GENERAL INFORMATION ON LMSR-SPT VK / -HK

- Dynamic Probing DPL, DPM, DPH and SPT
- Window Sampling up to 80 mm diameter
- Modular drop weight system with 63.5 kg out of 750 mm dropping heights maximum
- Maximum blow energy: 467 Joule
- **○** Blows per Minute: 15-30

- Dimensions
 785 mm x 780 mm x 2,600 mm
- Three-leg foot for perpendicular working in all positions
- Blow counter
- Accessoires and all needing tools included



LMSR-SPT ON TRAILER

- Hydraulic engine with 160 bar system pressure
- Dynamic probing DPL, DPM, DPH and SPT
- Dimensions 4,500 x 2,000 x 2,750 mm
- Allowed on public roads
- Also possible to work with hydraulic jack hammers and diamond coring bits

item number: 311092



YOUR CUSTOM-MADE LMSR

Your project demands the application of special rigs or you are looking for a custom-made rig adapted exactly to your method of operation? We are happy to design for you your custom-made LMSR.

Please contact us for a non-binding offer

CONTACT



Nordmeyer GEOTOOL GmbH

Weststraße 6

16356 Werneuchen

Germany

Tel: +49 (0) 33398 9142 0 **Fax:** +49 (0) 33398 9142 22

Mail: info@nordmeyer-geotool.de
Web: www.nordmeyer-geotool.com