

SOIL INVESTIGATION RIG



INFORMATION STANDARD RIG

SOIL INVISTIGATION RIG PR 530

FULLY HYDRAULIC ON CRAWLER CHASSIS

item number: 312012



- The PR 530 replaces its predecessors PR 440 and PR 510, which were successful drilling rigs.
 The PR 530 is the smallest drilling rig by Nordmeyer GEOTOOL. Compactness and practicality have once more been our goal.
- The crawler, equipped with a fast mode, is easy to handle. The machine has very precise steering and high ground stability.
- The extremely short mast is fully hydraulic. No manual adjustment is necessary.


- The pneumatic penetrometer for DPM, DPH and SPT and window sampling can be quickly replaced by a DPL configuration.
- The PR 530 can perform easily window sampling with rods up to 80 mm with 460 Joule and 35 strokes/min.
- The integrated extraction can easily and quickly extract different rods.
- Connectors for compressed air tools faciliting certain work.

DIMENSIONS

Width: 790 mm

Length: 1.900 mm in transport position Height: 1.400 mm in transport position

Mast height: 3.100 mm in working position Weight: 580 kg (with lifting unit)



FURTHER OPTIONS

SPECIAL EQUIPMENT

Pneumatic penetrometer for DPM, DPH and SPT and window sampling

- · Hydraulic unit with traction mecanism and extraction device
- · Connectors for the hydraulic and compressed air
- · Transport support for rods and tools
- · Support for long window sampler
- · Hydraulic driven compressor for pneumatic ram probing and compressed air

Caracteristics

- Chassis: mechanical crawler transmission: 2 forward and reverse speeds
- 4-stroke gasoline engine, 270 cc, 9 HP
- Pneumatic operating pressure: Max 1,2 bar/ Compressed air max. 6 bar
- · Hydraulic operating pressure: 160 bar
- · Hydraulic volume: approx. 22 liter, tank volume 20 liters

Drop weight

- · Weight: Basic weight: 30 kg, additional weight of 20 kg and 13,5 kg
- Fall height: 0,5 m and 0,75 m

Additional equipment

DPL ram probing
 item numb

Tool box attached to the special support

item number: 106634

The PR530 can be equipped with the following lifting units

• Extraction Jack 90 kN

Extraction Jack 140 kN
 item number: 101186

Extraction Jack 190 kN
 item number: 101187





Nordmeyer GEOTOOL GmbH Weststraße 6 16356 Werneuchen Germany Tel.: +49 (0) 33398 9142 0
Fax: +49 (0) 33398 9142 22
Mail: info@nordmeyer-geotool.de
Web: www.nordmeyer-geotool.com